



нейтральный проводник, с опережающим срабатыванием, для фронтального крепления, до 32 А,, принадлежность для главных и аварийных выключателей 3LD2

версия			
торговая марка изделия	SENTRON		
наименование изделия	нейтральный проводник		
исполнение изделия	принадлежности для главного и аварийного выключателя 3LD2		
номер американского калибра проводов (AWG) как кодируемое поперечное сечение подключаемого провода			
• мин.	14		
• макс.	8		
вид подключаемых сечений проводов для главных контактов			
• тонкожильный с заделкой концов кабеля	1 x (1,5–16 мм²)		
• однопроводной или многопроводной	1 x (1,5–10 мм²)		
General Product Approval		Test Certificates	other



[Confirmation](#)



[Special Test Certificate](#)

[Confirmation](#)

other	Environment
Miscellaneous	Environmental Confirmations

Дополнительная информация
Информация об упаковке
Информация об упаковке
Information- and Downloadcenter (Catalogs, Brochures,...)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3LD9220-0B
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/ru/ps/3LD9220-0B
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9220-0B
CAX-Online-Generator
http://www.siemens.com/cax
Tender specifications



