



система DELTA i, цвет: электрический белый
лицевую панель розетка UAE пригодно для Ackermann, кат. 3 2 x 8 --пол., 55x55 мм

версия	
торговая марка изделия	DELTA
наименование изделия	Защитная крышка, для UAE-розетки, кат.3, двойная
исполнение изделия	Обмен данными
исполнение защитной крышки	55 мм x 55 мм
исполнение компоновки	Центральная плата
Общие технические данные	
вид монтажа	скрытый монтаж
обработка поверхности	прочее
комплектация изделия надпись	Нет
материал	термопласт
класс защиты	
степень защиты IP	IP20
пригодность	
пригодность к использованию	UAE/IAE
появление	
внешний вид	глянцевый
цветовой код RAL	1013
цвет	цвет: электрический белый
Подробнее	
компонент изделия	
<ul style="list-style-type: none"> • поле для надписей • откидная крышка • разгрузка от натяжения 	Нет Нет Нет
характеристика изделия	
<ul style="list-style-type: none"> • безгалогенный • прозрачный 	Да Нет
Механическая конструкция	
высота	55 мм
вид креплений	винтовое крепление
материал	пластмасса
General Product Approval	other

[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=5TG1208>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/5TG1208>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TG1208

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



