



SENTRON, цилиндрическая вставка предохранителя, класс CC, 20 А, инерц., Un AC: 600 В, следует соблюдать национальные правила монтажа ! защита регулирующих трансформаторов, дросселей, катушек индуктивности

версия	
торговая марка изделия	SENTRON
наименование изделия	Цилиндрическая предохранительная вставка
Общие технические данные	
эксплуатационный класс вставки предохранителя	Инерционный
размер плавкой вставки предохранителя	Класс срабатывания CC
тип напряжения рабочего напряжения	Переменный ток
рабочее напряжение при переменном токе расчетное значение	600 V
Главная цепь	
рабочий ток ном. значение	20 A
Подробнее	
компонент изделия боек-индикатор	Нет
Механическая конструкция	
монтажное положение	Произвольно, предпочтительно вертикально
масса нетто	8 g
<b>General Product Approval</b>	
<b>Declaration of Conformity</b>	



[Confirmation](#)



EG-Konf.

other

[Miscellaneous](#)

[Confirmation](#)

## Дополнительная информация

Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3NW1200-0HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/3NW1200-0HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NW1200-0HG](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NW1200-0HG)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



