



система DELTA i, карбон металл лицевую панель розетка UAE
пригодна для Rutenbeck, кат. 3+5/ BTR кат. 6, 55x55 мм

версия		
торговая марка изделия		DELTA
наименование изделия		Крышка, для UAE-розетки
исполнение изделия		Обмен данными
исполнение защитной крышки		55 мм x 55 мм
исполнение компоновки		Центральная плита
Общие технические данные		
вид монтажа		скрытый монтаж
обработка поверхности		прочее
комплектация изделия надпись		Нет
материал		термопласт
класс защиты		
степень защиты IP		IP20
пригодность		
пригодность к использованию		UAE/IAE
появление		
внешний вид		глянцевый
цветовой код RAL		7016
цвет		черный металлик
Подробнее		
компонент изделия		
• поле для надписей		Нет
• откидная крышка		Нет
• разгрузка от натяжения		Нет
характеристика изделия		
• безгалогенный		Да
• прозрачный		Нет
Механическая конструкция		
высота		55 mm
вид креплений		винтовое крепление
материал		пластмасса
General Product Approval		Test Certificates
		other

Confirmation

Miscellaneous

Miscellaneous

Confirmation



Информация об упаковке

[Информация об упаковке](#)

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=5TG1227>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/ru/ps/5TG1227>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TG1227

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



