



проходная клемма нейтрального проводника, фронтальный монтаж, принадлежность для выключателей-разъединителей 3LD3

версия		
торговая марка изделия	SENTRON	
наименование изделия	проходная клемма нейтрали	
исполнение изделия	принадлежности для выключателя-разъединителя 3LD3	
номер американского калибра проводов (AWG) как кодируемое поперечное сечение подключаемого провода		
• мин.	14	
• макс.	6	
начальный пусковой крутящий момент при клеммном соединении рекомендуемый	3 N·m	
вид подключаемых сечений проводов для главных контактов		
• тонкожильный с заделкой концов кабеля	1 x (2,5–15 мм²)	

General Product Approval	other	Environment
Confirmation	Miscellaneous	Confirmation
		Environmental Confirmations

Дополнительная информация
Информация об упаковке
Информация об упаковке
Information- and Downloadcenter (Catalogs, Brochures,...)
http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/ru/ru/Catalog/product?mlfb=3LD9340-2B
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/ru/ps/3LD9340-2B
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9340-2B
CAX-Online-Generator
http://www.siemens.com/cax
Tender specifications
http://www.siemens.com/specifications



